

	Specification
Model	HT8420T
Size	4.3" (L:W = 16:9)
Resolution	480 X 272
Brightness	400cd/m ²
Color	262,144 Color
Contrast	400:1
COM Port	1
Network Port	1
USB Device Port	1
USB Main Port	1
SD Card	Nil
Backlight	50000 Hours
Touch Screen	4 Lines High precision Touchpad, 3 Million Single Point Touch Lifespan
Communication	USB, RS232, RS422, RS485
User Memory	12M
Power Supply	DC24V (±15%)
Power	3W
CE Certificate	Comply with EN50022 & EN50024 Standard
FCC Compatibility	Comply with FCC, Class A
Voltage Isolation	1000VAC @ 1Minute
IP Rating	IP65 (Front Panel)
Working Temperature	-10 - 65°C
Working Humidity	10 - 90%RH (Non-Condensate)
Cover Casing	ABS+PC
Dimension	173 X 96 X 39mm
Mounting Hole Size	165 X 86mm
Weight	About 0.2kg
Engineering Tools	HT8000CN V1.0.0

HT8700T, HT8700TE, HT8720T Detail Specification

	Specification		
Model	HT8700TE	HT8700T	HT8720T
Network Port	1	0	0
USB Main Port	1	1	1
SD Card	1	0	1
Dimension (mm)	228 X 154 X 41		203 X 145 X 40
Mounting Hole Size (mm)	211 X 145		192 X 138
USB Device Port	1		
COM Port	2		1

Size	7" (L:W = 16:9)
Resolution	800 X 480
Brightness	450cd/m ²
Color	262, 144 Color
Contrast	450:1
Backlight	50000 Hours
Touch Screen	4 Lines High precision Touchpad, 3 Million Single Point Touch Lifespan
Communication	USB, RS232, RS422, RS485
User Memory	12 M
Power Supply	DC24 V (±15%)
Power	6 W
CE Certificate	Comply with EN50022 & EN50024
FCC Compatibility	Comply with FCC, Class A
Voltage Isolation	1000VAC @ 1Minute
IP Rating	IP65 (Front Panel)
Working Temperature	-10 - 65°C
Working Humidity	10 - 90%RH (Non-Condensate)
Cover Casing	ABS+PC
Weight	About 1.5 kg
Engineering Tools	HT8000CN V1.0.0

	Specification	
Model	HT8A20TE	HT8A20T
Network Port	1	0
USB Main Port	1	1
SD Card	1	0
USB Device Port	1	
COM Port	2	
Size	10.2" (L:W = 16:9)	
Resolution	800 X 480	
Brightness	500cd/m ²	
Color	262, 144 Color	
Contrast	450:1	
Backlight	50000 Hours	
Touch Screen	4 Lines High precision Touchpad, 3 Million Single Point Touch Lifespan	
Communication	USB, RS232, RS422, RS485	
User Memory	12 M	
Power Supply	DC24V (±15%)	
Power	7 W	
CE Certificate	Comply with EN50022 & EN50024 Standard	

FCC Compatibility	Comply with FCC, Class A
Voltage Isolation	1000VAC @ 1Minute
IP Rating	IP65 (Front Panel)
Working Temperature	-10 - 65°C
Working Humidity	10 - 90%RH (Non-Condensate)
Cover Casing	ABS+PC
Dimension (mm)	266 X 208 X 40
Mounting Hole Size (mm)	261 X 203
Weight	About 2.0 kg
Engineering Tools	HT8000CN V1.0.0

HT8C20T Detail Specification

	Specification
Model	HT8C20T
Network Port	1
USB Main Port	1
SD Card	1
USB Device Port	1
COM Port	2
Size	12.1" (L:W = 4:3)
Resolution	800 X 600
Brightness	450cd/m ²
Color	262,144 Color
Contrast	450:01:00
Backlight	50000 Hours
Touch Screen	4 Lines High precision Touchpad, 3 Million Single Point Touch Lifespan
Communication	USB, RS232, RS422, RS485
User Memory	12 M
Power Supply	DC24V (±15%)
Power	8 W
CE Certificate	Comply with EN50022 & EN50024 Standard
FCC Compatibility	Comply with FCC, Class A
Voltage Isolation	1000VAC @ 1Minute
IP Rating	IP65 (Front Panel)
Working Temperature	-10 - 65°C
Working Humidity	10 - 90%RH (Non-Condensate)
Cover Casing	ABS+PC
Dimension (mm)	338 X 253 X 65
Mounting Hole Size (mm)	330 X 246
Weight	About 2.26 kg
Engineering Tools	HT8000CN V1.0.0

HT8E20T Detail Specification

	Specification
Model	HT8E20T
Size	15"
Resolution	1024 X 768
Touch Screen	5 Lines Resistive Touch Screen
Backlight Module	LED
Contrast	600:01:00
Brightness (cd/m ²)	350
CPU	Intel Atom N450, 1.66GHz Single Core, 5.2KB Cache
OS	Support Windows XP/XPE, Windows 2000 SP4
Chipset	Intel ICH8M
RAM	Built in 1GB DDRII RAM, Expandable RAM 1GB SO-DIIMM DDRII
Network	1 X 10/100/1000Mbps Auto Negotiation
Display	Support up to 1400 X 1050 @60Hz
Audio	Built in HD Audio, Support MIC-IN/Speaker-out
Storage	2.5" 320G SATA Hard Disk, Support CF Type II
BIOS	4MB
VGA Port	1
RJ45 Network Port	1
Audio Port	2
COM Port	4
USB2.0 Port	4
DC Power Supply Port	1
PS/2 Mouse/Keyboard	1
Working Temperature	0-50° C
Input Power Supply	AC 100-240V 50-60Hz
Output	DC 24V 5A
Input Voltage	24VDC
Power	30W
Working Humidity	10-95%RH
Vibration	5-17Hz/1.0mm Amplitude
Dimension (mm)	395 X 320 X 48mm
Mounting Hole Size (mm)	267 X 292 X 40.4
Weight	5.9KG
Safety Certificate	CE, FCC