



MODEL T2000-TSS-01

MODEL T2000-TSS-02

Cargo Liquid Sampling Device for liquid sampling

Specification

Tape length	15 m / 30 m / 40 m
Tape graduation	Metric
Tape resolution	1 mm
Tape accuracy	± 3.2 mm / 30m
Top coupling (Connection)	PF 2-1/4" TAP
Weight	TSS-01 12.4 kg / 15m
	TSS-02 9.1kg / 30m
Overall dimensions (H × W × T)	TSS-01 APP. 1112 × 346 × 180 mm
	TSS-02 APP. 950 × 346 × 180 mm
Capacity of Sampling bottle	0.5 Liter



MODEL T2000-TLS-01

Tank Bottom Liquid and Sediments Checking Device for tank bottom dryness checking, etc.

Specification

Tape length	30 m / 40 m / 50 m
Tape graduation	Metric
Tape resolution	1 mm
Tape accuracy	± 3.2 mm / 30 m
Top coupling (Connection)	PF 2-1/4" TAP
Weight	5.0 kg / 50M
Overall dimensions (H × W × T)	APP. 850 × 310 × 75 mm



MODEL T2000-TOS-01

Inert Gas Sampling Hose & Adaptor for oxygen and flammable gas concentration measuring

Specification

Hose size	O.D 8 x I.D 6 mm
Hose length	20 m / 35 m / 45 m
Top coupling (Connection)	PF 2-1/4" TAP
Weight	3.5 kg / 35 m



MODEL T2000-TPG-01

Pressure Gauge for inert gas pressure

Specification

Pressure range	-1000 to 3000 mmHzO
Accuracy	1.5% of full scale
Top coupling (Connection)	PF 2-1/4" TAP
Weight	1.2 kg



MODEL TVC-01

Top Conn. : PF 2-1/4" TAP
 Flange Conn. : 25A JIS 5K EF
 or 50A JIS 5K F.F
 Function : Vapor Lock Installation
 of PMS Bottom Dryness
 Checking, Etc.



MODEL TVC-02

Top Conn. : PF 2-1/4" TAP
 Flange Conn. : 50A JIS 5K EF
 or 80A JIS 5K F.F
 Function : Vapor Lock Installation of
 PMS Main Tank
 Gauging Station
 (Ullage Gauging & Sampling)



MODEL TVC-04

Top Conn. : PF 2-1/4" TAP
 Flange Conn. : 100A JIS 5K F.F
 Function : Vapor Lock Installation of
 PMS Main Tank
 Gauging Station
 (Ullage Gauging & Sampling)

Shut On / Off Valve (Vapor Control Valve) for tank gauging station