

Clicker Press

Clicker Press - Auto-Pneumatic Clicker Press

This low-cost and high quality Pneumatic clicker press only requires air with min. 73 psi (5 bar) pressure to operate and is widely used in the rubber and plastics industry for accurately cutting rubber, plastics, and leather specimens. The Auto-Pneumatic clicker press is available in 3 or 5 ton capacities suitable to cut rubber samples with thickness up to 10 or 15mm respectively. This compact, cost effective and high quality sample cutting press can be used for any testing laboratory.

- Excellent Quality-Performance/Price Ratio
- Simple operation
- Features safety buttons
- Only requires 5 bars of air pressure for operation

Specifications of Auto-Pneumatic Clicker Press:

APC-3000	APC-5000
Size: 18" x 12" x 26"	Size: 18" x 16" x 35"
Cutting pressure: 3 Tons	Cutting pressure: 5 Tons
Weight: 60 kg	Weight: 120 kg
Power: Pneumatic	Power: Pneumatic
Air requirement: 5 Kg/cm ² (prepared by customer)	Air requirement: 5 Kg/cm ² (prepared by customer)
Thickness of Specimen (Max.): 10mm	Thickness of Specimen (Max.): 15mm
Effective space (WxDxH): 18 x 8 x 8 cm	Effective space (WxDxH): 40 x 34 x 8.5 cm

