

1507008000

Ballast non explosion proof

1507 2X400 HS 3 6 IP67 PFC 3XM24-12.5

Elnumber:

EAN-nr: 4036538110221

Stock code: A



Ballast units are applicable for decks and holds, industrial areas and sport areas. The ballasts are designed according to rules of maritime classification.



Technical data	
Maximum ambient temperature (°C)	45
IP classification	67
Dimensions	
Net weight (kg)	13,2
Height (mm)	135
Width (mm)	260
Length (mm)	455
Gross weight (kg)	13,5
Body	
Colour of body	White
Body material	Stainless Steel AISI 316L
Body colour code	RAL 9016
Electrical data	
Minimum frequency -5% (Hz)	60
Maximum frequency +5% (Hz)	60
Maximum voltage +10% (V)	230
Minimum Voltage -10% (V)	220

Ballast/Driver	
Number of ballast/driver	2
Type of ballast/driver	High power factor correction
Light data	
Number of lamps	2
Lamp power (W)	400
Light source	HS
Termination	
Number of cable glands	1
Type of cable gland	M24-Brass
Minimum cable diameter	10
Maximum cable diameter	12.5
Remarks	
Remarks	Housing with earth-outside. Cable entry: 3xM24x1.5 brass D10-12.5mm MGCG

1507008000

Ballast non explosion proof

Drawings

