

Designation:	Exterior light / EXEL-230L / 56W	Symbol:	
Supplier:		Supplier ArtNo.:	
Manufacturer:	Cortem Group	Manufacturer ArtNo.:	EXEL-230L

Electrical data	
Voltage [V]: 220-240	Current [A]:
Ambient Temp [°C]: -40 / +40	Battery backup:
	Frequency [Hz]: 50/60
	Total consumption [W]: 56

Luminaire description	
Type: EXEL-230L	Light source: LED
Technology CC:	Consumption [W]: 56
CV:	No of illuminants: 2
Trafo incl.: Y	Dimmable:
Illuminant incl.: Y	Lum flux [lm]: 5637
CRI Index: 80	Beam angle [°]: 120
	Colour temp [K]: 5000

Mechanical description	
Housing: plastic	Color: black
Reflector: white aluminium	Prot. class: IP66
Diffuser: translucent polycarbonate	Fire class:
Surface height [mm]:	Weight [kg]: 9.20
Dimens. [mm] L: 185.00	Cover ring:
W: 1370.00	Ø:
H: 155.00	Cut out [mm]:
LED stripe cutting space [mm]:	Delivery length [m]:
Lum. flux per metre [lm/m]:	Bend. radius [mm]:
Mounting: surface mounted	
Equipment: 4x connection holes for M25x1.5 (through-wiring) / complete with 3 blind plugs and 2 cable glands UNI2LXE7DS (Ø10-18mm)	

Power supply / Dimmer	
Designation:	
Prot. class:	Weight [kg]:
Dimension [mm] L:	
W:	
H:	
Ø:	
Designation:	
Prot. class:	Weight [kg]:
Dimension [mm] L:	
W:	
H:	
Ø:	
Remarks:	

Remarks:	- LIGHT.FIXT. EX II 2GD EX DE MB IIC - Ex II 2GD Ex mb op is IIC T5 Gb / Ex tb IIIC T64 ° C ° C Db IP66 (T6 / T64 ° C + 40 ° C a.inquiry) - shock and UV resistant - tub made of black impact-resistant and UV-resistant - reclining frame: aluminium and stainless steel - with electr. ballast and Ex de safety switch
----------	---

