

Designation: Exterior light / EXEL-236 / 36W

Symbol:

Supplier:

Supplier ArtNo.:

Rev: 0

Manufacturer: Cortem Group

Manufacturer ArtNo.: EXEL-236

Electrical data

Voltage [V]: 100-240

Current [A]:

Frequency [Hz]: 50/60

Ambient Temp [°C]: -40 / +55

Battery backup:

Total consumption [W]: 72

Luminaire description

Type: EXEL-236

Light source: Consumption [W]: 2 x 36

Technology CC: CV: Trafo incl.: Illuminant incl.: Y Dimmable: No of illuminants: 2

CRI Index: Beam angle [°]: Colour temp [K]: Lum flux [lm]:

Mechanical description

Housing: fibreglass / poly. resin Color: black Prot. class: IP66 Fire class:

Reflector: white aluminium Diffuser: transparent polycarbonate Cover ring: Weight [kg]: 7.90

Surface height [mm]: Dimens. [mm] L: 185.00 W: 1370.00 H: 155.00 Ø: Cut out [mm]:

Rec. mnt. height [mm]: LED stripe cutting space [mm]: Delivery length [m]:

LED spacing [mm]: Lum. flux per metre [lm/m]: Bend. radius [mm]:

Mounting: surface mounted

Equipment: 4x through holes for ISO M25 (3 blind plugs and 2 cable glands made of plastic incl.)

Power supply / Dimmer

Designation:

Prot. class: Dimension [mm] L: W: H: Ø: Weight [kg]:

Designation:

Prot. class: Dimension [mm] L: W: H: Ø: Weight [kg]:

Remarks:

- Remarks:
- LIGHT.FIXT. EX II 2GD EX DE MB IIC
 - Ex II 2GD Ex de mb IIC T4 Gb Ex tb IIIC T70 / 80 ° C Db IP66
 - GRP wall light for 2x36W 110 / 240Vac / dc 50 / 60Hz
 - with electronic ballast



Code	Dimensions mm			
	A	A1	B	C
EXEL-236	1370	720	185	155

