KÜHTREIBER® ///

KIT 400 WS

STANDARD

30-350 A

310 A/60%



DESCRIPTION

KIT 400 WS are professional welding machines equipped with a high-powered transformer with copper primary and secondary winding, robust all-metal wire feeder with an efficient motor, an EURO connector and electronics control.

The main advantages of machine KIT are excellent welding skills, 40-grade voltage control, high power, high duty cycle, high reliability and very easy operating.

USAGE

All machines are designed for medium and heavy machinery production, construction, metalproduction, ship-production or maintenance plants.

Code	50284
Input power 50/60 Hz [V]	3x400
Protection – slow [A]	25
Welding current range [A]	30 – 350
Output voltage range [V]	18 – 40
Duty cycle 100 % [A]	260
Duty cycle 60 % [A]	310
Duty cycle 30 % [A]	350
Mains current/input 60 % [A/kVA]	15.3/10.6
Winding	Cu
Number of adjustment points	40
Digital volt-ampere meter	yes
Wire feeder	4-roll
Standard equip roll	1.0 – 1.2
Wire feeder speed [m/min]	1 – 20
Material of wire – Steel, Stainless steel – Aluminium – Cored wire	•
Ingress Protection	IP 21
Dimensions [mm]	1263 × 620 × 871
Weight [kg]	145
FEATURES	
2-STROKE / 4-STROKE	•
BURN BACK	•
EASY USE	•
PRE-GAS / POST-GAS	•
SPOT PULS	•
FEED BACK	•
GENERATOR	•

W - The W variant includes a liquid cooling circuit for

a welding torch.