

# Generator F90 - H115

## Cylinder

- Double wall steel cylinder (machined, polished and chromium plated)
- Cylinder external insulation (polystyrene sheets)
- Cylinder external insulation liner (PVC sheet)

## Base

- Insulated plate
- Generator base lid
- Vertical water pump
- Over flow connection
- Float valve for water supply
- PVC coated and insulated stainless steel base
- Connection pipe for water distribution
- Water drainage

## Revolving part

- Central shaft (zinc plated, painted steel) revolving between two ball bearings (zinc plated, painted steel)
- Lower water collection tray (stainless steel)
- Upper water distribution tray (stainless steel)
- Vertical deflector (stainless steel)
- Reamer adjuster with bolts and nuts
- Helical reamer (stainless steel)
- Rubber wiper to limit the sprinkling area

## Drive for revolving part

- Torque limiter device with manual reset
- Gear reducer, motor and belt

## Refrigerating part

- Thermostatic expansion valve
- Horizontal heat exchanger
- Heat exchanger insulation (soft insulation)

## Miscellaneous

- Vertical salt dosing pipe requiring sodium chloride tablets (25 kg supplied)

## Options

- *Electrical control panel*
- *Remote control*
- *Ice level detector*
- *Salt dosing pump*



**GENEGLACE s.a.s.**

ZAC de la Forêt - 9, rue des Orfèvres  
44840 Les Sorinières - France

Tél. +33-(0)2-51-19-10-51 Fax +33-(0)2-40-05-73-81

**Scope of our supply**  
**Generator F90 - H115**  
**SEMI-INDUSTRIAL LAND-BASED**

Edition date 20/08/2004

V1.0

**GTL.001A**

**GENEGLACE may change this document without prior notice**