

Generator F90 - H115

Operating conditions

Refrigerant	Refrigerant charge (approx.)	Reamer speed	Water T°	Daily ice production	Ice thickness	Evap. T°	Refrigerating capacity	Max cond. T°
	kg	tr/h	°C	kg/24h	mm	°C	W	°C
R22	5	92	15	2700	2	-19,5	13500	55
R404a	5	92	15	2700	2	-19,5	13500	40
R22	4	58	15	1900	2,2	-14	9500	50

Refrigerant inlet

Thermostatic expansion valve

Electrical connections

Qty.	Description	Power supply	Nominal power	Amperage
1	Reamer motor	400 V - 3 - 50 Hz	1 x 180 W	1 x 0,8 A
1	Pump	230 V - 1 - 50 Hz	1 x 70 W	1 x 0,35 A
1	Torque limiter switch	-		

Overall dimensions

Length	925 mm
Width	775 mm
Height	1020 mm
Net weight	230 kg

Options

- *Electrical control panel.*
- *Ice level detector.*
- *Remote control.*
- *Salt dosing pump.*



GENEGLACE s.a.s.

ZAC de la Forêt - 9, rue des Orfèvres
44840 Les Sorinières - France

Tél. +33-(0)2-51-19-10-51 Fax +33-(0)2-40-05-73-81

Specifications

Generator F90 - H115

SEMI-INDUSTRIAL LAND-BASED

Edition date 15/12/2005

v1.0

GTD.001A

GENEGLACE may change this document without prior notice

Cancels and replaces the document of 01/04/2004